

# Heavy Duty Dissolved Oxygen Meter

Dual display of oxygen concentration and temperature plus RS-232 PC interface

## Features:

- Super large 1.4" (36mm) LCD display
  - Dual display of oxygen and temperature
  - Measures dissolved oxygen from 0 to 20.0mg/L and 0 to 100.0% oxygen plus temperature from 32 to 122°F (0 to 50°C)
  - Automatic Temperature Compensation from 0 to 50°C via temperature probe sensor built into polarographic type oxygen probe
  - Fast 0.8 second sampling time
  - Recall Min/Max/Average readings
  - Data Hold
  - Built-in RS-232 PC serial interface with optional data acquisition software and datalogger
  - Auto power off saves battery life
- Kitted complete with 0.8" (20mm) diameter probe on 44" (1.1m) cable, 5 membranes, rubber holster, 9V battery and hard vinyl carrying case
- Optional Windows® Data Acquisition Software and serial cable enable user to display and capture readings on a PC, and set time intervals and alarms
  - Optional battery operated Datalogger module stores over 8000 readings for later transfer to a PC



Specifications:	Dissolved Oxygen	Oxygen	Temperature
Range:	0 to 20.0 mg/L	0 to 100.0%	32 to 122°F (0 to 50°C)
Accuracy:	±0.4 mg/L	±0.7%	±0.8°C/1.5°F
Probe Compensation & Adjustment:	Salt: 0 to 39%	Altitude: 0 to 3900m	Temp: 0 to 50°C
Dimensions/Weight:	7x2.9x1.3" (178x74x33mm) / 17oz (meter only) Probe: 20mm(0.8")D 125mm(4.9")L		

## Ordering Information:

407510 .....Heavy Duty Dissolved Oxygen Kit

### Accessories:

780407 .....Replacement Membranes (5/pack)  
780408 .....KCL Solution  
156119 .....117 VAC Adaptor  
156221 .....220 VAC Adaptor

### Options:

407001 .....Data Acquisition Software and cable  
380340 .....Battery operated Datalogger Module

EXTECH INSTRUMENTS CORPORATION  
285 Bear Hill Road, Waltham, MA 02451-1064, U.S.A.  
Phone: 781-890-7440 • FAX 781-890-7864

ISO 9001:2000 CERTIFIED

Make mine an Extech!  
[www.extech.com](http://www.extech.com)



02/02 - R1