

## Digital StrobeTach

Freeze motion and measure speed without contact

### Features:

- Checks and analyzes motion and speed by simply aiming and synchronizing its flash rate (FPM) with a rotating object
- Read RPMs on 4 digit LED display
- Duty cycles from 5 to 30 minutes and 1second sampling time
- Ideal for measuring the speed of moving gears, fans, pumps, motors and other equipment used in general maintenance, production, quality control or laboratories
- High accuracy over a wide, dynamic range via exclusive microcomputer LSI circuit and crystal control time-base
- Complete with 6 ft power cord, handle and can be tripod mounted.



Specifications:	
Flash/Speed Rate:	100 to 10,000 FPM/RPM
Accuracy:	±(0.05%rdg +1 digit)
Duty Cycle:	5 to 30 minutes
Sampling Time:	1 second
Dimensions:	8.3 x 4.8 x 4.8" (211x122x122mm)
Weight:	2.2 lbs. (1 kg)

### Ordering Information:

461830 .....Digital StrobeTach 115 VAC, 60Hz  
461831 .....Digital StrobeTach 220 VAC, 50Hz  
461834 .....Spare Xenon Lamp (est life 300 hrs)

EXTECH INSTRUMENTS CORPORATION  
285 Bear Hill Road, Waltham, MA 02451-1064, U.S.A.  
Phone: 781-890-7440 • FAX 781-890-7864

ISO 9001:2000 CERTIFIED

Make mine an Extech!  
[www.extech.com](http://www.extech.com)



08/03 - R1